

FREQUENCY	I/2 MILE	2 MILE
(Hz)	(dB)	(dB)
100	131.3	146.4
150	128.8	142.5
200	126.8	140.1
250	125.4	138.2
300	124.4	136.8
350	123.4	135.7
400	122.7	134.9
450	122.1	134.2
500	121.6	133.8
550	121.2	133.5
600	120.8	133.3
650	120.5	133.2
700	120.2	133.2
750	120.0	133.3
800	119.8	133.4
850	119.6	133.6
900	119.4	133.8
950	119.3	134.2
1000	119.2	134.5
1050	119.1	134.9
1100	119.0	135.4

TABLE A: REQUIRED SOUND PRESSURE LEVELS AT

I METER FOR 1/2 AND 2 MILE FOG SIGNALS

§ 67.10-25 Application for tests.

A person requesting a Coast Guard representative at a test of a sound signal must:

- (a) Direct a written request to the Office of Aids to Navigation, (CG-541), 2100 2nd St., SW., Stop 7581, Washington, DC 20593-7581 including:
- (1) Requestor's name, address, and telephone number;
- (2) A description of the sound signal;
- (3) Rated range for which approval is requested;
- (4) Location of the anechoic chamber; and
 - (5) Proposed test dates.
- (b) Bear all the expenses of conducting the test conducted in accordance with \$67.10-20 including all travel and per diem expenses of the U.S. Government in sending a Coast Guard representative to the test.

[CGD 72–74R, 37 FR 13512, July 8, 1972, as amended by CGD88–052, 53 FR 25119,July 1, 1988; CGD 96–026, 61 FR 33663, June 28, 1996; USCG–2001–10714, 69 FR 24983, May 5, 2004; USCG–2010–0351, 75 FR 36281, June 25, 2010]

§67.10-30 Withdrawal of approval.

The Coast Guard may withdraw approval of a sound signal if it fails to

meet the requirements of §67.10-1 (a), (b), and (c).

§ 67.10-35 Notice of approval and withdrawal of approval.

- (a) The Coast Guard publishes a notice of the approval or withdrawal of approval of a sound signal in the Local Notice to Mariners.
- (b) A listing of approved sound signals may be obtained from any District Commander.

§ 67.10–40 Sound signals authorized for use prior to January 1, 1973.

Any sound signal authorized for use by the Coast Guard and manufactured prior to January 1, 1973, is excepted from the requirements in this subpart, except §§67.10–1 (b) and (c), 67.10–5, and 67.10–10, if the sound signal has a minimum sound pressure level as specified in Table A of Subpart 67.10 of Title 33 of the Code of Federal Regulations in effect on December 31, 1972, for the range required by §67.20–10, §67.25–10, or §67.30–10.